

Hydraulic Series Scissor Lifts

0608S/M(1930S/1932M)

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

Product Highlights

Efficient and environmentally friendly

- Small turning radius, flexible operation in narrow spaces
- Standard forklift slot, for efficient equipment transportation
- Folding guardrails for easy transport

Reduced maintenance costs

- Double-door design for easy maintenance
- Troubleshooting for quick fault diagnosis
- High quality parts and components

More reliable performance

- Battery voltage early warning to ensure battery life
- Bumper rail protection
- The pothole protection reporting and horizontal protection system guarantee safety of operation

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Full-stroke operation
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic painting technology
■ 4x2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	■ Overload sensing system
■ Integrated hand shield	■ Automatic pothole guard	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

SINOBOOM

Sinoboom Intelligent Equipment Co Ltd

📍 No.128 East Jinzhou Av., Ningxiang Hi-Tech Industry Park,
Changsha, Hunan, China, 410600

🌐 www.sinoboom.com

✉ sales@sinoboom.com

Hydraulic Series Scissor Lifts

0608S/M(1930S/1932M)

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

SINOBOOM

Model		0608S/M(1930S/1932M)
Dimensions		
Max Working Height		7.8m(25'7")
A Max Platform Height		5.8m(19')
B Max Horizontal Extension		0.9m(3')
C Length-Stowed		1.78m(5'10")
D Width-Stowed		0.76m(2'6")/0.81m (2'8")
Height	Stowed(Rail Folded)	1.86m(6'1")
	E Stowed (Rail Unfolded)	2.12m(6'11.5")
	Stowed(Fixed Rail)	2.12m(6'12")
	Stowed(Fixed Rail)	2m(6'7")
F Wheelbase		1.325m(4'4")
Ground Clearance		70mm(2.8")
Platform Dimensions(L×W×H)		1.64m×0.76m×1.1m(5'5"×2'6"×3'7")
Performance		
Platform Allowable Occupants (Indoor/Outdoor)		2 persons/1 person
Platform Capacity		230kg(507lbs)
Drive Speed-Stowed		3km/h(1.86mph)
Drive Speed-Raised		0.8km/h(0.5mph)
Elevation Time(Unloaded)		15s~20s
Descent Time(Unloaded)		25s~30s
Gradeability		25%
Turning Radius(Inside/Outside)		0/1.49m(0/4'11")
Tilt Rating(Front to Back/Side to Side)		3°/1.5°
Tyre Size/Type		305×115mm(12"×5")/solid
Power		
Batteries		6V×4/225Ah
Power Source		24V DC
Drive Mode		2WD, front wheel
Charger Input		100~240V AC
Charger Output		30A
Brake		2 rear wheel
Hydraulic System Capacity		14L(3gal)
Weight		
Weight(Indoor/Outdoor)		1,526kg(3,365lbs)
Standards Compliance		

